

Guangdong Sanvo Chemical Industry Technology Limited Safety Data Sheet

1. Identification of Chemicals and Manufacturer

English name of chemical: SANVO High Performance Thread Sealant SH-100

Manufacturer: Guangdong Sanvo Chemical Industry Technology Limited

Address: Dacen Industrial Park, Huangpu Town, Zhongshan City, Guangdong, China

Postal Code: 528429. CHINA

Telephone: 0760-28163797

Company Emergency telephone number: 0532-83889090

Fax number: 0760-28163118

E-mail address: sanvo@sanvo.com

Recommended use: Thread locking and sealing of metal parts

2. Hazards Identification

	EMERGENCY OVERVIEW
WARNING:	CAUSES SKIN IRRITATION.
	MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.
	MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

Health hazards

Skin irritation	Category 2
Eye irritation	Category 2A
Skin sensitization	Category 1
Specific target organ system toxicity primary contact	Category 2

Label elements Pictograms

Hazard statement Prevention

Response



Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.



Storage

Not prescribed

Disposal

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

3. Component/ Composition Information

Substance/mixture	Mixture	
Chemical Entity	CAS No.	Proportion (%)
Epoxy acrylic resin	71281-65-7	50-55
Hydroxypropyl methacrylate	27813-02-1	30-40
Diethylene glycol dibenzoate	120-55-8	7-15
Cumene hydroperoxide	80-15-9	3-5
O-sulfonylbenzoimide	81-07-2	3-5
Complexing agent	60-00-4	1-3
DCP	80-15-9	1-3
Promoter	/	0.1-1
Polymerization inhibitor	/	0.1-0.5
Dyeing	/	0.5-1

4. First aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

5. Fire-fighting measures

Extinguishing media:Water spray (fog), foam, dry chemical or carbon dioxide.Special firefighting procedures:Wear self-contained breathing apparatus and full protective clothing, such as
turn-out gear. In case of fire, keep containers cool with water spray.



Unusual fire or explosion hazards:	Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.
Hazardous combustion products:	Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic vapours.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedure

For non-emergency personnel	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean- up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.	
For emergency responders	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.	
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.	
Clean-up methods and materials		
and containment measures	Stop leak if you can do so without risk. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.	
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.	
7. Handling and storage		
Handling	Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8	
Storage	For safe storage, store at or below 38 °C (100.4 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.	

8. Exposure Controls / Personal Protection

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Engineering measures:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched



to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.

Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Hand protection:

Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC). Viton/butyl.

Eye protection:


Wear safety glasses with side shields (or goggles).

Skin and body protection:

Wear appropriate chemical resistant clothing.

9. Physical and chemical properties

Appearance	
Physical state	Liquid
Color	Red
Odor:	Mild
Odor threshold	Not available
pH value:	Not applicable.
Melting point/freezing point (°C)	Not available.
Boiling point/range:	> 148.9 °C (> 300°F)
Initial boiling point (°C)	Not available.
Boiling range (°C)	Not available.
Flash point (°C)	> 93.3 °C (> 199.94 °F) Tagliabue closed cup
Flammable/Explosive limits -lower: Flammable/Explosive limits - upper: Specific gravity	Not available. Not available. 1.1
Vapor density	Not available.
Vapor Pressure (kpa)	<5 mm hg(26.7°C(80.1°F)).
Ralative Vapor density (air = 1)0Solubilityother organic solvents.	.83~0.88 Slightly soluble in water, soluble in esters, aromatic, chloroform and
N - octanol/water distribution coeffic Auto-ignition temperature Flammability	cient Not available. Not available. Not applicable



11. Toxicological information

Relevant routes of exposure:Potential Health Effects/SymptomsInhalation:Inhalation of vapors or mists of the product may be irritating to the respiratory system.Skin contact:Causes skin irritation. May cause allergic skin reaction.Eye contact:Causes serious eye irritation.Ingestion:May cause gastrointestinal tract irritation if swallowed.

12. Ecological information

Environmental destruction and distribution: possible pollution of air and water. Low toxicity to fish and mammals.

Persistence and degradation: volatile components can be photolyzed, and steam residues can be slowly oxidized and degraded by organisms and microorganisms.

Toxicity: it has the potential of low toxicity and biochemical enrichment to prevent the growth of organisms and Microorganisms.



13. Disposal considerations

Residual waste: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

Local disposal regulations: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. Transport information

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)		
Proper shipping name:	RQ, Environmentally hazardous substance, liquid, n.o.s.	
Hazard class or division:	9	
Identification number:	UN 3082	
Packing group:	III	
DOT Hazardous Substance(s):	alpha,alpha-Dimethylbenzylhydroperoxide	
International Air Transportation (ICAO/IATA)		
Proper shipping name:	RQ, Environmentally hazardous substance, liquid, n.o.s.	
Hazard class or division:	9	
Identification number:	UN 3082	
Packing group:	III	
Water Transportation (IMO/IMDG)		
Proper shipping name:	RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	
Hazard class or division:	9	
Identification number:	UN 3082	
Packing group:	III	

15. Regulatory Information

Regulatory information:

Regulations on the safety management of hazardous chemicals (order 344 of the state council)

Measures for the administration of hazardous chemicals registration (order No. 35 of the state economic and trade commission)



Regulations on the registration and administration of hazardous chemicals in Guangdong province (Guangdong economic and trade security [2003] No. 80)

Regulations on the safe use of chemicals in the workplace ([1996] No. 423 issued by the department of labor) Relevant provisions are made for the production, operation, storage, transportation, use and disposal of hazardous chemicals.

16. Other information

Literary reference

- 1. Global uniform classification and labelling of chemicals (second revision), 2007
- 2. Model regulations for the transport of dangerous goods ,2015
- 3. International maritime dangerous goods (edition 34-08)
- 4. Technical manual for hazardous chemical safety, Chemical industry press, 1997
- 5. Regulations on the safety management of hazardous chemicals, 2011
- 6. Dangerous goods list (GB12268-2012)
- 7. Classification and code of dangerous goods (GB6944-2012)
- 8. Compilation of technical specification for hazardous chemical safety (GB16483-2000)
- 9. Classification and marking of common hazardous chemicals (GB13690-92)

Professional training: personnel engaged in the handling or transportation of dangerous goods must receive

training on the content of requirements related to the handling or transportation of dangerous goods, general knowledge or familiarity training, specific functional training and safety training, etc.

Issued: October 28, 2020

Drafting Department: Aerosol Research Institute of Guangdong Sanvo Chemical Industry Technology Limited. Data Audit Unit: Guangdong Sanvo Chemical Industry Technology Limited. Version: 1.0