

SANVO MULTI-PURPOSE ANTIRUST LUBRICANT

Product Description

It is made by a unique formula. It can form a protective film on the surface of the object to isolate moisture and prevent oxidation/rust.

Suitable for anti-rust lubrication of equipment, precision instruments and other objects.

Applications

It can be widely used for corrosion resistance of precision instruments, accessories, electrical contact points, steel parts and highly sensitive components.

It can eliminate the friction noise from door hinges, iron gates, motor vehicle parts and chairs.

Features

- Good permeability
- Strong lubricity
- Good moisture removal
- Moisture removal
- Noise elimination
- Both lubrication and rust prevention

Typical Properties

Composition	Anti-rust lubricant, Kerosene, Dispersant, LPG
Specific Gravity	0.810~0.840/cm ³
Appearance	No wear and tear, accurate and clear code without leakage
Odour	No odour
Permeability	Good
Gas tightness (50±1℃)	Good
Anti-rust performance	Good
Lubricity	Good
Volatile speed	Faster
Filling ratio	Max 85% of the total volume of can
Spray Rate	≥96%
Shelf life	3 years





TECHNICAL DATA SHEET



Instructions

1. The surface must be thoroughly cleaned and free of other contaminants.
2. Shake the product well, insert the tube, and spray the required parts to prevent backward spraying.
3. Spray or fully soak this product on the parts to be treated.

Precautions

1. Do not use near flames, sparks, direct sunlight, heat and etc.
2. This product is pressure-packed.
3. Do not expose to heat beyond 50°C.
4. Do not puncture and incinerate the can.

Disposal of waste can

Invert the can body and press the nozzle for about 2 minutes to remove the remaining liquid. If necessary, remove the nozzle completely.

Packing/Size

Each can has a volume of 400 ml.
12 cans are packed in a carton.