

## SANVO Anaerobic Flange Sealant SH-515

### Product Description

SANVO Anaerobic Flange Sealant SH-515 is a kind of modified acrylic resin glue, which is cured by isolating air between two closely matched metals. It has good chemical resistance, good flexibility, high temperature resistance (+ 150 °C), anti-corrosion and other excellent properties. It can provide more reliable sealing than traditional pre cut gasket.

### Applications

It seals close fitting joints between rigid metal faces and flanges and will flex with minor flange movements. Typically used as a form-in-place gasket for pumps, thermostats, compressors, transmission housings and axle covers.

### Features

- Good flexibility, excellent resistance to corrosion.
- Resistant to shock, chemical and high temperature of 150°C.
- Ideal for machined metal components.

### Technical Data

|                         |                           |
|-------------------------|---------------------------|
| Color                   | Purple                    |
| Appearance              | Glue                      |
| Base                    | Dimethylacrylate ester    |
| Application Temperature | Apply above 50°F (10°C)   |
| Set Time                | ≤30 minutes               |
| Service Temperature     | -55°C to 150°C            |
| Viscosity               | 150000-400000mPa.s/25±2°C |
| Shelf life              | 24 months                 |



### Storage and Disposal

Not damaged by freezing. Close the tube tightly after each use. Store product in the unopened container in a dry location. Optimal storage is between 46°F (8°C) to 70°F (21°C).

### Packing/Size

50g × 40pcs/carton