

Sanvo fine interior wall paint

Product Description

It adopts a unique "anti-fouling additive" formula, which can form a strong protective barrier on the surface of the paint film and effectively prevent the residual traces of the paint film; With high covering power, smooth handle, super easy to wash and long-lasting bright paint film, it is the first product of luxury decoration.

Applications

Interior decoration of various residences, hotels and projects, including concrete, brick wall, plasterboard and other surfaces.

Features

1. High hiding power.
2. Smooth feel.
3. Easy to wash.
4. Lasting bright paint film.

Typical Properties

Colour	White or according to the needs of color
Component	Acrylic copolymer emulsion, stain resistant additives, pigments and fillers, auxiliaries and water.
Packing	Toilet iron
Loading capacity	20kg
Dilution ratio	0~20%
Construction temperature	5℃~35℃
Recoating time	>2h
Maintenance time	7Days / 25 °C
Storage conditions	Frost free and dry
Consumption / layer thickness	8~ 10m ² / kg / layer (dry film 30 micron meter)



TECHNICAL DATA SHEET



Instructions

1. Basic treatment:

New wall: remove the surface dust, grease and loose putty, if there is a gap should be repaired, the wall to be painted must be clean, dry and flat.

Repainting the wall surface: remove the weak paint film on the old wall surface, remove the dust on the surface, and polish the wall surface. Ensure that the wall to be painted is firm, clean, dry and flat without loose objects.

2. Spraying: use airless spraying.

3. Roller coating / brush coating: use roller coating and brush, pay attention to achieve a specific dry film thickness.

Transportation and storage

1. This product is non-flammable and explosive material, which can be transported as general goods. During transportation, it is necessary to prevent rain, sun exposure and freezing, avoid extrusion and collision, and keep the packaging intact.

2. Under normal transportation and storage conditions (0 ~ 35 °C), the shelf life is 18 months.

Packing/Size

20kg/ barrel