

TECHNICAL DATA SHEET



SANVO Line Marking Paint

Product Description

SANVO Line Marking Paint is an aerosol type thermoplastic acrylic self-drying paint, with high content of solid content, good storage stability, good film adhesion, rapid drying, excellent covering rate, abrasion resistance, and UV resistance, which can meet long-term outdoor marking effect. This product is equipped with unique valves and buttons, and adopts inverted spraying construction. The marking width can be adjusted between 60mm and 130mm. It can meet the marking requirements of most widths. It can be operated by a single person. It is simple and fast. The constructor is comfortable and tidy. The line effect is neat and beautiful, which is the best choice for your marking products.

Applications

Suitable for roads, parking lots, stadiums, entertainment venues, warehouses, factory workshops and other workshops where various width and color markings are sprayed. It can be used for marking on the surface of asphalt, concrete, wood, metal and other materials.

Ideal Application Temperature

Between 10°C and 30°C. Avoid use in windy conditions.

Features

- Sharp and durable lines.
- Better opacity.
- Adjustable line width (60-130mm).
- Robust industrial quality.
- Applicator does not need cleaning after use.

Typical Properties

Composition: acrylic resin, organic solvent, filler, toner, propellant DME

Density, g/cm³: yellow 1.067±0.05, white 1.35±0.05

Coverage: 70mm continuous spraying 45-55m (depending on moving speed and colour used).

Drying time: 8 minutes surface drying (25°C); 2 hours hard drying (25°C)

Filling rate: white 76%, yellow 87%

Use places: parking lots, factories, warehouses, sports fields and stadiums, etc.

Spray effect: flat and smooth, consistent with standard board

Version 2.0, revised on 10/03/2021
Guangdong SANVO Chemical Industry Technology Limited
Email: export@sanvo.com
Web: <http://www.sanvochemicals.com>